

# SINGLE STAGE



## GEOSOURCE GEOTHERMAL HEAT PUMPS 2 - 6 Ton Forced Air

**A GeoSource geothermal heat pump by Enertech** will supply all of your heating and cooling needs for a fraction of what you are paying with fossil fuels. You could save up to 70%! GeoSource helps contribute to a greener and healthier environment because geothermal heating and cooling comes from the energy that is stored in the ground. By installing a new GeoSource unit, you will have done the equivalent of planting 750 trees or removing two cars from our highways. Not only are you saving money, but you are saving energy and helping to save the environment.

**The GeoSource product family offers** industry leading efficiencies combined with specialized optional bundle packages to provide you with the ultimate comfort experience.

**GeoSource Energy Star Tier 3 performers.** Take advantage of the 30% tax credit as well as local, state, and utility incentives that are available! Enertech heat pumps are manufactured in the United States and backed by an ISO 9001 based quality management system, so you can be sure that you are getting a top quality, reliable system that will stand the test of time.



**Our ENERGY STAR® qualified heat pumps qualify for the 30% federal tax credit.**

\*Check [www.gogogeo.com](http://www.gogogeo.com) for current list

**A Better Way to HEAT & COOL YOUR** 

**GEOSOURCE™**

# TOTAL COMFORT »

- **Whisper-quiet technology**  
-reduces cabinet noise through vibration isolation
- **On-demand domestic hot water**  
-provides 100% of your domestic hot water heating needs (optional)
- **Active control panel**  
-lets you know the system is operating and when it is providing heat, cooling, or hot water
- **Broad offering of unit types and sizes**  
-ensures your dealer can provide a system that is just right for you

- Lower bills by up to **70%**
- Qualifies for the **30%** federal tax credit
- Payback in as little as **5** years

## SINGLE STAGE BY THE NUMBERS »

(Tested in accordance with ASHRAE/AHRI/ISO Standard 13256-1)

Ground Loop (ARI/ISO 13256-1)			Heating 32°F EWT		Cooling 77°F EWT	
Models	CFM	GPM	BTU/hr	COP	BTU/hr	EER
RGS-V024	1,000	6	19,000	3.7	26,000	17.6
RGS-V036	1,000	9	27,500	3.6	36,800	17.1
RGS-V048	1,600	12	37,500	3.7	51,000	17.3
RGS-V060	1,800	15	48,400	3.6	60,600	17.1
RGS-V072	2,100	18	66,000	3.6	79,000	17.1

Ground Water (ARI/ISO 13256-1)			Heating 50°F EWT		Cooling 59°F EWT	
Models	CFM	GPM	BTU/hr	COP	BTU/hr	EER
RGS-V024	1,000	6	25,000	4.5	30,400	22.0
RGS-V036	1,000	9	34,500	4.3	41,000	22.0
RGS-V048	1,600	12	47,000	4.4	58,000	22.0
RGS-V060	1,800	15	59,800	4.1	65,600	21.1
RGS-V072	2,100	18	81,000	4.1	82,000	21.1



Technical data subject to change. Due to continuous product enhancements, please refer to [www.gogogeo.com](http://www.gogogeo.com) for the most current performance data.

180-00049 | 20DEC2012C | ©2012 EnerTech Global, LLC

